

# AKHL1260E



MODEL	AKHL1260E(CE)
DIMENSIONS	337 (H) x 309 (W) x 583 (L) mm
WEIGHT	16.2 kg
MAX WORKING PRESSURE	34 bar
MOTOR POWER	2 HP
POWER SUPPLY	230 V / +/-10% 50Hz +/-1%
RATED CURRENT	6 A
CYLINDERS	2 cylinders
RATED SPEED	2,800 rpm
TANK VOLUME	8.6 L
PRESSURE SWITCH WORKING RANGE	Off : 34bar / On : 30bar

# AKHL1260EX



MODEL	AKHL1260EX(CE)
DIMENSIONS	479 (H) x 380 (W) x 583 (L) mm
WEIGHT	23.3 kg
MAX WORKING PRESSURE	34 bar
MOTOR POWER	2 HP
POWER SUPPLY	230 V / +/-10% 50Hz +/-1%
RATED CURRENT	6 A
CYLINDERS	2 cylinders
RATED SPEED	2,800 rpm
TANK VOLUME	21.5 L
PRESSURE SWITCH WORKING RANGE	Off : 34bar / On : 30bar

It is one push to change to silent mode

2 outlets for high pressure nailer and 2 outlets for 8 bar pressure nailer

Coupling compressors



## Accessories

Attachable additional 3 tanks for AKHL1260E "AKTH13"

Additional tank connection chuck "TT05022" for AKHL1230E and AKHL1250E

Air Chuck 44K Purge "TT05029" for AKHL1260E

Max High pressure air hose drum "SD630A2"

Air pressure reducer "ZT99998"

44-44K Connecting Hose AK14754

